

摩托车启动锂离子电池 HJTZ5S -FPZ Lithium Battery for Motorcycle Start HJTZ5S -FPZ		
SIZE : L 113mm x W 69mm x H 85mm 		
性能参数 Specification		
额定电压 Nominal Voltage	12V	
额定容量 Nominal Capacity	3.0Ah	
重量 Weight	Approx.0.7kg	
充电电压 Charging Voltage	14.4±0.5V	
充电电流 Charging Current	STD.: 1.5A; MAX.: 15.0A	
高倍率放电 High Rate Discharge (60A, 25C°)	5s Voltage ≥10.0V, 30s Voltage ≥7.2V	
高倍率放电 High Rate Discharge (60A, 0C°)	5s Voltage ≥7.2V, 30s Voltage ≥7.2V	
CCA Tested by Digital Tester: (A)	210	
操作温度 Operating Temperature	充电 Charge	0~45C°
	放电 Discharge	-10~60C°
	储存 Storage	-20~40C°
循环寿命 Cycle Life	≥1000 (100%DOD, 25C°)	
自放电 Self Discharge	25C°下可储存1年以上（温度越高时间越短），使用前检查电池电压，若电压低于12.8V需充电 Battery can be stored for more than 12 months at 25C° (for higher temperature the self discharge will be faster). Check the battery voltage before using, recharge it if battery voltage less than 12.8V.	
充电曲线 Charge Characteristic	循环寿命曲线 Cycle Life Feature	
工厂证书 Certificates	IATF16949; ISO9001; IS14001; ISO18001	
产品证书 Product Certificate	UL1642 cell inside; CE; RoHs; UN38.3	